



ART. 023/A

ART. 023/C

ART. 023/A 1 Hose Barb Outlet

ASTM A270 Tri-Clamp - Flange design according to ASME-BPE

Size	Ø B	L	Valve Material	O-Ring Material	Code
1/2"	6,00	38,00	1.4404	FPM/FKM	023A60050 V
				EPDM	023A60050 EP
				SILICONE FDA	023A60050 SIF
3/4"	6,00	38,00	1.4404	FPM/FKM	023A60075 V
				EPDM	023A60075 EP
				SILICONE FDA	023A60075 SIF

Int. finishing: $Ra \leq 1,2 \mu m$ Ext. finishing: $Ra \leq 1,6 \mu m$ mirror polished

Max Working Conditions:


6 bar (87 psi) and 150°C (300°F)

Installation:


Horizontal installation recommended**ART. 023/C** 1 Hose Barb Outlet + 1 CIP Hose Barb Inlet

ASTM A270 Tri-Clamp - Flange design according to ASME-BPE

Size	Ø B	L	Valve Material	O-Ring Material	Code
1/2"	6,00	38,00	1.4404	FPM/FKM	023C60050 V
				EPDM	023C60050 EP
				SILICONE FDA	023C60050 SIF
3/4"	6,00	38,00	1.4404	FPM/FKM	023C60075 V
				EPDM	023C60075 EP
				SILICONE FDA	023C60075 SIF




ART. 023/A




ART. 023/C

Spare parts



ART. 023/A



ART. 023/C

N°	Name	Material
1	Body	AISI 316L
2	Piston	AISI 316L
3	O-Ring 2025	FPM/FKM or EPDM or SILICONE FDA
4	M3 Screw	AISI 304
5	Handle	AISI 316L
6	Seeger	AISI 304

N°	Description	Valve size	Code
2	Piston - n° 1 pcs	all sizes	AAAA0381
3	O-Ring Kit 2025 FPM/FKM - n° 5 pcs	all sizes	ORNSV05V
3	O-Ring Kit 2025 EPDM - n° 5 pcs	all sizes	ORNSV05EP
3	O-Ring Kit 2025 SILICONE FDA - n° 5 pcs	all sizes	ORNSV05SIF
5	Handle - n° 1 pcs	all sizes	AAAA0380
6	Seeger - n° 10 pcs	all sizes	SEEGERSV